

NOT JUST BETTER IN EVERY WAY. THE BEST IN EVERY WAY.



Introducing **LYNX**

The LYNX Series bottom-loading couplers represent a new era from OPW Engineered Systems. We've completely reimagined what an API dry-break coupler can be. Effortless handling. Advanced safety features. Minimal leakage. And perhaps most impressive: incredibly quick and easy disassembly of the entire coupler thanks to a revolutionary U-pin design.



EASY TO USE, EASY TO MAINTAIN, WITH A WARRANTY THAT MAKES IT EASY TO LOVE.

LYNX



Unique U-pin
design enables disassembly of
the coupler in 30 seconds.

✓ **Better Sealing**
New Seal Design = Less Dripping

✓ **Wave Spring**
3x More Life!

✓ **Handle Shaft**
Significantly Stronger

✓ **Stainless-Steel Collar**
Durability for Life

✓ **Links/Camplates**
Added Strength

✓ **4 True-Interlocking Latches**



Max Surge Pressure of 500 psi

ORDERING

LYNX852	Long Handle*, Viton® B70
LYNX852VG	Long Handle*, Viton® GFLT
LYNX852B	Long Handle*, Nitrile/Buna
LYNX852F	Long Handle*, Fluorosilicone
LYNX852ULT	Long Handle*, Ultra Low-Temp (FKM)

* Also Available with Short Handle.

Distributed by:

信德迈科技(北京)有限公司
北京朝阳区望京SOHO-T1-C座2115室 邮编: 100102
010-8428 2935 , 8428 9077 , 139 1096 2635
QQ: 3031901644
sales@cnmec.biz

SPECIFICATIONS

Max Working Pressure:	80 psi
Test Pressure:	120 psi
Max Surge Pressure:	500 psi
Operating Temp:	-49°F to 200°F (-45°C to +93°C)*
Design Standard:	API RP 1004 8th Edition
Weight:	19 lbs.

*Operating temp. rating will vary based on seal selection