

NOT JUST BETTER IN EVERY WAY. THE BEST IN EVERY WAY.



Introducing **LYNX**

The LYNX Series bottom-loading couplers represent a new era from OPW Engineered Systems. We've completely reimagined what an API dry-break coupler can be. Effortless handling. Advanced safety features. Minimal leakage. And perhaps most impressive: incredibly quick and easy disassembly of the entire coupler thanks to a revolutionary U-pin design.



www.opw-es.com/lynx

EASY TO USE, EASY TO MAINTAIN, WITH A WARRANTY THAT MAKES IT EASY TO LOVE.

LYNX



Unique U-pin
design enables disassembly of
the coupler in 30 seconds.

 **Better Sealing**
New Seal Design = Less Dripping

 **Stainless-Steel Collar**
Durability for Life

 **Wave Spring**
3x More Life!

 **Links/Camplates**
Added Strength

 **Handle Shaft**
Significantly Stronger

 **4 True-Interlocking Latches**




Max Surge Pressure of 500 psi

ORDERING

LYNX852	Long Handle*, Viton® B70
LYNX852VG	Long Handle*, Viton® GFLT
LYNX852B	Long Handle*, Nitrile/Buna
LYNX852F	Long Handle*, Fluorosilicone
LYNX852ULT	Long Handle*, Ultra Low-Temp (FKM)

* Also Available with Short Handle.

Distributed by:



SPECIFICATIONS

Max Working Pressure:	80 psi
Test Pressure:	120 psi
Max Surge Pressure:	500 psi
Operating Temp:	-49°F to 200°F (-45°C to +93°C)*
Design Standard:	API RP 1004 8th Edition
Weight:	19 lbs.

*Operating temp. rating will vary based on seal selection



www.opw-es.com ◆ 2726 Henkle Drive ◆ Lebanon, Ohio 45036 ◆ Phone: (513) 932 9114 ◆ Fax: (513) 932 9845

NOTE: All information subject to engineering and/or other changes. All trade names are copyrighted. Patents Pending. ©2016 OPW Engineered Systems. ©2016 Delaware Capital Formation, Inc. All Rights Reserved. DOVER and the DOVER logo are registered trademarks of Delaware Capital Formation, Inc., a wholly-owned subsidiary of Dover Corporation.